

# Compact permanent magnet spectrometer for CILEX/APOLLON

Francesco Massimo, Martin Khojoyan ICAP 2018, October 20-24, USA

- > Introduction
- > Design and construction of a permanent dipole magnet
- > Measurement and characterization of the magnet as a spectrometer at CILEX
- > Summary

### > Introduction

> Design and construction of permanent dipole magnet

Measurement and characterization of the magnet as a spectrometer at CILEX

≻ Summary

# **CILEX** project

#### GALOP: Groupe d'Acceleration Par Laser et Ondes Plasma





Electron acceleration using PW lasers

Electron transfer line for multi-stage acceleration

LLR (A. Specka) coordinates first experiments and is responsible for electron spectrometer design

### > Introduction

- > Design and construction of permanent dipole magnet
- Measurement and characterization of the magnet as a spectrometer at CILEX
- ≻ Summary

### Magnet design: Introduction







Peak field in the gap as function of permanent magnet width for the gap height of 0.1 mm.

#### Peak field in the gap cannot exceed remnant induction field of the magnet !

# Design of PM dipole: Analytic estimation



Schematic view of top half of H shaped magnet. Iron parts are shown in yellow, and surrounding magnets blue colors.

$$B_g^* = \frac{1}{h_g} \frac{(w_1 + w_2 + w_3)B_r}{\left(\frac{w_g}{h_g} + \frac{\mu_r w_1}{h_1} + \frac{\mu_r w_2}{h_2} + \frac{\mu_r w_3}{h_3}\right)}$$



Peak magnetic field vs. total weight of the surrounding magnets. Red asterisk represents the values assuming 51 mm square pole sizes (w<sub>pole=w2</sub>) for 10 mm gap height (2h<sub>g</sub>).

\* Bruce C. Brown, Fermilab/Conf-96/273, 1996.

# Design of PM dipole: Numerical calculation

$$h_1 = h_3 = 5.08 cm$$
  $w_1 = w_3 = 7.08 cm$   $h_2 = w_2 = 5.08 cm$   
 $\stackrel{-}{\overset{-}{0}}_{0} 2.2$   
 $\stackrel{-}{\overset{-}{0}}_{0} 2.2$   
 $\stackrel{-}{\overset{-}{0}}_{0} 1.8$ 

20

0

40

o

50

60



30

Gap height, mm

#### **Details**

Maximum f

1.4

1

0

10

0.6

The pole pieces are made of iron ( $\sim 2.26$  T saturation field) NdFeB 40 magnets are used to construct the dipole (Br  $\sim 1.24$  T) A fixed ratio (20) of magnet length to gap height in TOSCA



TOSCA model of magnet with 2.09 T in gap (2.18 T pole saturation field).

#### Summary of magnet characteristics .

| Parameter                    | Value           |
|------------------------------|-----------------|
| Gap height, mm               | 10              |
| Peak field at gap center, T  | 2.092           |
| Horizontal GFR / FGR, mm     | 50 / 150        |
| Length x height x width , mm | 100 x 260 x 240 |
| Weight, kg                   | ~ 50            |

### PM dipole: Construction



Overview of different block magnets used to assembly the dipole. Arrows on the blocks illustrate directions of magnetization.



Measured magnetic induction at the surface of two types of neodymium magnets. For each case, black lines represent analytically estimated field value assuming 0.5 mm offset of Hall probe sensor from the magnet surface.

#### Geometry of iron poles will smoothen field inhomogeneities once the pole material is saturated !

- > Introduction
- > Design and construction of permanent dipole magnet
- Measurement and characterization of the magnet as a spectrometer at CILEX
- ≻ Summary

### PM dipole: Measurements I



Measurement bench at LLR.



On and off-axis main component field profiles along horizontal and longitudinal directions. For each case dots correspond to the measured and curves to the simulated field values.

# PM dipole as a spectrometer II



#### E-beam parameters used in ASTRA

| Parameter                | Value     |
|--------------------------|-----------|
| Charge, pC               | 10        |
| Peak current, kA         | 1.2       |
| Energy, MeV              | 56 - 2350 |
| Transverse rms size , μm | 2.5       |
| Rms divergence, mrad     | 2         |

Reference electron trajectories and corresponding screen positions/ orientations for energy measurement inside the interaction chamber of CILEX.

56 MeV  $\rightarrow$  the lowest energy exiting magnet from side

2350 MeV  $\rightarrow$  the highest energy measurable out of 50 mrad divergent laser cone

### Beam size and resolution





Beam rms transverse sizes at screen positions of S1 and S2. Blue line: horizontal, red rectangles: vertical.

Rms energy resolution estimated at different screens for 2 milliradians electron beam divergence.

□ Electrons of energies below 200 MeV are strongly affected by the fringe field (FF) effects

□ The FF effects may be modified by adjusting the magnet laterally

 $\leq 8$  % resolution over the whole energy range !

### > Introduction

> Design and construction of permanent dipole magnet

Measurement and characterization of the magnet as a spectrometer at CILEX

≻ Summary

### Summary

- 2.1 Tesla PM dipole was designed measured and characterized as a spectrometer for CILEX
- Very good agreement (~ 1 %) between predicted and realized field values
- □ The magnet will cover energy range of ~ [0.06-2.35] GeV with less than 10 % resolution (without additional focusing)

### Thank you !